


NERC Lessons Learned

Kevin Hatch Manager, Reliability Engineering



Load Shed Sequence

Rapid Decrease in Generation Causes Frequency Drop



PUBLIC

ercot 😓

12



NERC Lessons Learned



Managing Under Frequency Load Shed Obligations





- February 2021 cold weather event required load shed for system reliability
- Entities found it difficult to rotate customer outages while maintaining service to critical loads & UFLS feeders
- Percentage of system load connected to UFLS feeders exceeded the required percentage levels
- Some system operators ultimately ran out of non-UFLS and noncritical load circuits and were forced to use a portion of their UFLS circuits to meet manual load shed directives



- - Several TOPs noted that their UFLS-connected load represented up to 60% of its remaining load during the period of February 15–16

100
100 AD SHED

UFLS Percentages Excluding Load Resources (2/1/2021 - 2/28/2021)

Figure 1: February cold event UFLS connected load percentages (Feb 15-16 in blue shade area)



- TOP may have the option to use some of the UFLS "margin" to include in load shed and rotating outages while still meeting its UFLS obligations
- Critical loads should not all receive the same level of priority, and the characteristics of a load shed event (depth/duration/season) will impact the treatment of certain critical loads
- It is critical to have the flexibility to include or exclude certain facilities based on the load shed scenario



References

LL20220301 Managing UFLS Obligations Service Critical Loads during Energy Emergency

https://www.nerc.com/pa/rrm/ea/Lessons%20Learned%20Document%20Librar y/LL20220301_Managing_UFLS_Obligations_Service_Critical_Loads_during_ Energy_Emergency.pdf

https://www.puc.texas.gov/agency/resources/reports/UTAustin (2021) EventsF ebruary2021TexasBlackout (002)FINAL 07 12 21.pdf





Presenter: Kevin Hatch, Kevin.Hatch@pjm.com

SME: Kevin Hatch, Kevin.Hatch@pjm.com

NERC Lessons Learned

Member Hotline (610) 666 – 8980 (866) 400 – 8980 custsvc@pjm.com

